

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (Currently Amended) A catheter to be percutaneously inserted into a living body lumen, said catheter comprising:
 - a sheath portion having a lumen extending therein,
 - an insertion member slidably disposed in said lumen of said sheath portion and having a distal end portion capable of protruding from a distal end portion of said sheath portion, an injection needle disposed at said distal end portion of said insertion member for injecting a therapeutic composition into a target tissue in a living body, and
 - an electrode disposed at ~~[[a]]~~ said distal end portion of said catheter insertion member and spaced from a bevel of said injection needle disposed at said distal end portion of said insertion member for measuring a cardiac action potential.
2. (Original) The catheter as set forth in claim 1, wherein said target tissue is a cardiac tissue.
3. (Original) The catheter as set forth in claim 1, wherein said therapeutic composition contains a nucleic acid, a protein, or cells.

4. (Original) The catheter as set forth in claim 1, wherein said distal end portion of said sheath portion is provided with a through-hole communicated with said lumen.

5. (Original) The catheter as set forth in claim 4, wherein said through-hole is spaced by not less than 1 mm from an end face of said distal end portion of said sheath portion along the longitudinal direction of said sheath portion.

6. (Original) The catheter as set forth in claim 1, wherein a plurality of said electrodes are provided.

7. (Currently Amended) The catheter as set forth in claim 1, further comprising a second electrode ~~wherein said electrode is disposed at each of said distal end portion of said insertion member and/or said distal end portion of said sheath portion~~ for measuring a cardiac action potential.

8. (Canceled)

9. (Currently Amended) The catheter as set forth in claim ~~[[7]]~~ 1, wherein said electrode ~~disposed at said distal end portion of said insertion member~~ is located at an outer circumferential surface of said distal end portion of said insertion member.

10. (Currently Amended) The catheter as set forth in claim ~~[[9]]~~ 6, wherein ~~a plurality of~~ said electrodes are disposed at said distal end portion of said insertion member in the state of being spaced from each other along the longitudinal direction of said insertion member.

11. (Currently Amended) The catheter as set forth in claim ~~[[7]]~~ 1, wherein said electrode disposed at said distal end portion of said insertion member is spaced by not less than 1 mm from the ~~distal end~~ the bevel of said injection needle along the longitudinal direction of said insertion member.

12. (Currently Amended) A catheter system comprising:
a catheter to be percutaneously inserted into a living body lumen, said catheter comprising a sheath portion having a lumen extending therein, an insertion member slidably disposed in said lumen of said sheath portion and having a distal end portion capable of protruding from a distal end portion of said sheath portion, and an injection needle disposed at said distal end portion of said insertion member for injecting a therapeutic composition into a target tissue in a living body;

a first electrode disposed at ~~[[a]]~~ said distal end portion of said ~~catheter~~ insertion member and spaced from a bevel of said injection needle disposed at said distal end portion of said insertion member for measuring a cardiac action potential;

a second electrode for measuring said cardiac action potential; and

a puncture detection unit to which a conductor extending from said first electrode and a conductor extending from said second electrode are connected and which detects the puncture by said injection needle based on said cardiac action

potential measured by said first electrode and said second electrode.

13. (Original) The catheter system as set forth in claim 12, wherein said second electrode is disposed at a distal end portion of said catheter, and is located on the side of the proximal end of said catheter relative to said first electrode.

14. (Original) The catheter system as set forth in claim 12, wherein said second electrode is provided as a separate body independent from said catheter.

15. (Currently Amended) A method of injecting a therapeutic composition by use of a catheter to be percutaneously inserted into a living body lumen, said catheter comprising a sheath portion having a lumen extending therein, an insertion member slidably disposed in said lumen of said sheath portion and having a distal end portion capable of protruding from a distal end portion of said sheath portion, an injection needle disposed at said distal end portion of said insertion member for injecting said therapeutic composition into a target tissue, and ~~[[an]]~~ a first electrode disposed at ~~[[a]]~~ said distal end portion of said ~~catheter~~ insertion member and spaced from a bevel of said injection needle disposed at said distal end portion of said insertion member for measuring a cardiac action potential, said method comprising the steps of:

(a) inserting said catheter into a living body and advancing said catheter to the vicinity of said target tissue; and

(b) puncturing said target tissue by said injection needle and injecting said therapeutic composition into said target tissue through said injection needle, based

on said cardiac action potential measured by said first electrode.

16. (Currently Amended) The method as set forth in claim 15, wherein
~~said electrode is disposed at said distal end portion of said insertion member,~~
and

said step (b) comprises the steps of: moving said insertion member in the
distal direction relative to said sheath portion to thereby protruding said injection
needle from said distal end portion of said sheath portion, thereby puncturing said
target tissue by said injection needle, while measuring said cardiac action potential
by said first electrode; and

injecting said therapeutic composition into said target tissue through said
injection needle, after a change is detected in said cardiac action potential measured
by said first electrode.

17. (Currently Amended) The method as set forth in claim 15, wherein
said catheter further comprises ~~[[said]]~~ a second electrode ~~[[is]]~~ disposed at
said distal end portion of said sheath portion, and said step (b) comprises the steps
of:

bringing said distal end portion of said sheath portion into contact with said
target tissue while measuring said cardiac action potential by said second electrode;

detecting a change in the cardiac action potential measured by the second
electrode;

moving said insertion member in the distal direction relative to said sheath
portion to thereby protrude said injection needle from said distal end portion of said

sheath portion, thereby puncturing said target tissue by said injection needle, while further measuring said cardiac action potential by said second electrode, after the change is detected in said cardiac action potential measured by said second electrode; and

injecting said therapeutic composition into said target tissue through said injection needle, after it is confirmed that no change is generated in said cardiac action potential measured by said second electrode and said first electrode while moving the insertion member in the distal direction.